



SHEP CURE CITY WHITE E

WATER-BASED CONCRETE CURING COMPOUND

DESCRIPTION

Shep Cure City White E is a water based pigment liquid-membrane curing compound that is applied to freshly pour concrete surface, preventing rapid water evaporation. When the Shep Cure City White E compound is properly applied, the surface concrete forms an impermeable membrane, holding moisture in the concrete and keeping the freshly poured surface cooler, preventing cracking and crazing. Shep Cure City White E is an environmental product and does not contain any hydrocarbons like resins, solvents, or waxes.

PRIMARY APPLICATIONS

Shep Cure City White E is ideal when applying on concrete exterior surfaces such as highways, airports, streets, walkways, concrete slabs & curb paving.

SPECIFICATIONS

When tested in accordance to ASTM C309, Shep Cure City White E meets or exceeds water loss specifications of 2% at 24 hrs and 4% at 72 hrs after application, required by city and county specifications in the State of Texas.

TECHNICAL DATA

Drying Time..... Typically 2 – 3 hrs depending on temperature, humidity and application rate. Avoid traffic during this time period.

Flash Point..... Greater than 200° F

Density..... 8.7 ppg

Weight..... 8.7 ppg

Color..... Milky White

APPLICATION

- Apply Shep Cure City White E after the concrete receives its final finishing.
- Ideal use in Walkways, Curve sides, Home Slabs, City and County Streets.
- Apply by low pressure sprayer until saturation.
- Temperatures above 40°F are recommended.

COVERAGE

- Approximately 200 ft²/gal (4.91 m²/l)
- Coat uniformly, leave no gaps.
- For best results use a sprayer at 40 psi with a flow of ½ gallons per minute.

PRECAUTIONS

Do not mix or dilute with other compounds that contain solvents such as mineral spirits, or fluids that might contain petroleum distillates. This product is not recommended to be used in areas where other treatments are to be used including hardeners.

HEALTH HAZARDS

Follow instruction of SDS for Health and Safety Instructions.

STORAGE

Shep Cure City White E should be stored in tightly sealed factory containers. We recommend storage in a horizontal position to avoid moisture accumulation. Store it under roof if possible, especially if temperatures are below 40°F.

PACKAGING

- 5 Gal
- 275 Gal
- 55 Gal
- Bulk

WARRANTY

CMC Construction Services warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request. The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. CMC Construction Services. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As CMC Construction Services has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith