

# SHEP POXY ROADS & HIGHWAYS MEDIUM VISCOSITY



## 1. PRODUCT AND COMPANY IDENTIFICATION (PART A)

Company : Adhesive Technology Corp.  
 Address : 450 East Copans Road  
 Pompano Beach, FL 33064  
 Telephone : 800-892-1880  
 Emergency Phone : 800-225-3924 CHEM-TEL  
 Trade name : Ultrabond 2100-1 Part A  
 Product Use : Bonding & Coating

## 2. HAZARDS IDENTIFICATION (PART A)

### GHS Classification

### GHS Label

### Danger:

**Health:** Skin Irritant Cat 2  
 Eye Irritant Cat 2B  
 Carcinogen Cat 2

**Physical:** Not Classified

**Environmental:** Toxic to Aquatic Life Cat-2

### Emergency Overview

May cause skin sensitization  
 Causes skin and eye irritation  
 May cause cancer  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area

**Primary Route of Exposure:** Eyes, skin and oral

**Carcinogenicity:** This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.



Eye Irritant  
 Skin Irritant



Possible Carcinogen

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS (PART A)

Chemical Name	CAS #	% By Weight
Diglycidyl Ether of Bisphenol A	25085-99-8	60 - 100
Neopentyl glycol diglycidyl ether	17557-23-2	7 - 15
Titanium Dioxide	13463-67-7	0.1 - 1
Naphtha, Heavy Alkylate	64741-65-7	0.1 - 1

## 4. FIRST AID MEASURES (PART A)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

# SHEP POXY ROADS & HIGHWAYS MEDIUM VISCOSITY



## 5. FIRE FIGHTING MEASURES (PART A)

**Flash Point:** 204°C (>400°F)

**Flammable Limits:** N/A

**Extinguisher Media:** Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazards:** None known. Thermal decomposition products can be formed.

**Special Fire Fighting Procedures:** Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

## 6. ACCIDENTAL RELEASE MEASURES (PART A)

**Personal Precautions:** Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions:** Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

## 7. HANDLING AND STORAGE (PART A)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4°C and 35°C (40°F and 95°F).

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION (PART A)

### Exposure Guidelines

Component	CAS #	OSHA PEL	TLV
Titanium Dioxide	13463-67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

### Personal Protective Equipment:

**Respiratory Protection:** None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye / Face Protection:** Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

**Skin / Body Protection:** Wear suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment:** Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

## 9 PHYSICAL AND CHEMICAL PROPERTIES (PART A)

<b>Physical State:</b> Liquid	<b>Appearance:</b> White Liquid
<b>Evaporation Rate:</b> N/D	<b>Odor:</b> Slight Odor
<b>Odor Threshold:</b> N/D	<b>Melting/Freezing Point:</b> N/D
<b>Boiling Point and Range:</b> N/D	<b>Solubility in Water:</b> Insoluble
<b>Specific Gravity (g/cc):</b> 1.1	<b>Vapor Density (air = 1):</b> N/D
<b>Vapor Pressure:</b> N/D	<b>VOC Content:</b> N/D
<b>pH:</b> N/D	<b>Boiling Point:</b> N/D

# SHEP POXY ROADS & HIGHWAYS

## MEDIUM VISCOSITY



### 10. STABILITY AND REACTIVITY (PART A)

- Stability:** Stable
- Thermal Decomposition:** Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.
- Incompatibility:** Strong acids, peroxides, and other oxidizing agents.
- Conditions to avoid:** Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

### 11. TOXICOLOGICAL INFORMATION (PART A)

- Acute Oral Toxicity:** Not Determined
- Acute Dermal Toxicity:** Not Determined
- Acute Inhalation Toxicity:** Not Determined
- Skin Irritation:** Irritating to skin. The product has not been tested. The statement has been derived from the properties of the individual components.
- Eye Irritation:** Irritating to eyes. The product has not been tested. The statement has been derived from the properties of the individual components.
- Respiratory Irritation:** Inhalation of vapors or mists may cause lung irritation to the respiratory system.
- Sensitization:** May cause allergic skin reaction and irritation to the respiratory system. The product has not been tested. The statement has been derived from the properties of the individual components.
- STOT – Single Exposure:** Not Determined
- STOT – Repeated Exposure:** Not Determined
- Carcinogenicity Classification:**
- Titanium Dioxide:**  
IARC Group 2B: Possibly carcinogenic to humans. This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

### 12. ECOLOGICAL INFORMATION (PART A)

- Acute Toxicity for:**
- Fish:** Diglycidyl Ether of Bisphenol A:  
Fathead minnow/LC50 (96hrs): >3.1mg/L
- Aquatic Invertebrates:** Diglycidyl Ether of Bisphenol A:  
Water Flea Daphnis/EC 50 (48hrs): > 1.4 mg/L
- Algae:** No Data Available
- Microorganisms:** Diglycidyl Ether of Bisphenol A:  
Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/L
- Mobility:** Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

### 13. DISPOSAL CONSIDERATIONS (PART A)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

### 14. TRANSPORT INFORMATION (PART A)

This product is not regulated as a hazardous material for transportation.

# SHEP POXY ROADS & HIGHWAYS MEDIUM VISCOSITY



## 15. REGULATORY INFORMATION (PART A)

Further information: HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings		NFPA ratings	
Health:	2	Health:	2
Flammability:	1	Flammability:	1
Physical hazard:	0	Instability:	0
PPE:	B		



Hazard Rating: 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Severe, 4 = Extreme

### Federal Regulations:

**CERCLA RQ**

**SARA Title 311/312:** Not Determined

**CA Prop 65:** This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (Titanium Dioxide)

**TSCA:** Listed or Exempt

### State Regulations:

State RTK	Chemical Name	CAS #
NJ, MA, PA	Diglycidyl Ether of Bisphenol A	25085-99-8
	Titanium Dioxide	13463-67-7
	Naphtha, Petroleum, Heavy Alkylate (NJ,PA)	64741-65-7

## 16. OTHER INFORMATION (PART A)

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard.

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.

# SHEP POXY ROADS & HIGHWAYS MEDIUM VISCOSITY



## 1. PRODUCT AND COMPANY IDENTIFICATION (PART B)

Company : Adhesive Technology Corp.  
 Address : 450 East Copans Road  
 Pompano Beach, FL 33064  
 Telephone : 800-892-1880  
 Emergency Phone : 800-225-3924 CHEM-TEL  
 Trade name : Ultrabond 2100-1 Part B  
 Product Use : Bonding & Coating

## 2. HAZARDS IDENTIFICATION (PART B)

### GHS Classification

### GHS Label

### Danger:

**Health:** Skin Corrosion Cat 1B  
 Serious Eye Damage Cat 1  
 Carcinogen Cat 1  
 STOT Cat 2

**Physical:** Not Classified

**Environmental:** Toxic to Aquatic Life Cat-2



Causes severe skin burns and  
Eye damage



Carcinogen  
Possible organ damage

### Emergency Overview

Causes skin burns  
 Causes severe eye damage  
 May cause cancer  
 May cause damage to organs through prolonged or repeated exposure  
 May be harmful if inhaled  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area

**Primary Route of Exposure:** Eyes, skin and oral

**Carcinogenicity:** This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS (PART B)

Chemical Name	CAS #	% By Weight
Modified Polyamide	68953-36-6	20 - 35
Tris-2,4,6(dimethylaminomethyl)phenol	90-72-2	1 - 5
Modified cycloaliphatic Amine	770-35-4	15 - 30
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.1 - 1
Non Hazardous	Proprietary	30 - 50

## 4. FIRST AID MEASURES (PART B)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

# SHEP POXY ROADS & HIGHWAYS MEDIUM VISCOSITY



## 5. FIRE FIGHTING MEASURES (PART B)

**Flash Point:** >93°C (200°F)

**Flammable Limits:** N/A

**Extinguisher Media:** Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazards:** None known. Thermal decomposition products can be formed.

**Special Fire Fighting Procedures:** Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

## 6. ACCIDENTAL RELEASE MEASURES (PART B)

**Personal Precautions:** Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions:** Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

## 7. HANDLING AND STORAGE (PART B)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4°C and 35°C (40°F and 95°F).

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION (PART B)

### Exposure Guidelines

Component	CAS #	OSHA PEL	TLV
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.1 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

### Personal Protective Equipment:

**Respiratory Protection:** None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye / Face Protection:** Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

**Skin / Body Protection:** Wear suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment:** Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

## 9 PHYSICAL AND CHEMICAL PROPERTIES (PART B)

**Appearance:** Black Paste

**Odor:** Slight Odor

**Specific Gravity (g/cc):** N/D

**Vapor Pressure:** N/D

**pH:** N/D

**Evaporation Rate:** N/D

**Solubility in Water:** Insoluble

**Vapor Density:** N/D

**VOC Content:** ND

**Boiling Point:** N/D

# SHEP POXY ROADS & HIGHWAYS

## MEDIUM VISCOSITY



### 10. STABILITY AND REACTIVITY (PART B)

**Stability:** Stable

**Thermal Decomposition:** Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

**Incompatibility:** Strong acids, peroxides, and other oxidizing agents.

**Conditions to avoid:** Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

### 11. TOXICOLOGICAL INFORMATION (PART B)

**Acute Oral Toxicity:** Not Determined

**Acute Dermal Toxicity:** Not Determined

**Acute Inhalation Toxicity:** Not Determined

**Skin Irritation:** Corrosive to skin. The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:** Severe damage to eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:** Inhalation of vapors or mists may cause lung irritation to the respiratory system.

**Sensitization:** May cause allergic skin reaction and irritation to the respiratory system. The product has not been tested. The statement has been derived from the properties of the individual components.

**STOT – Single Exposure:** Not Determined

**STOT – Repeated Exposure:** CNS, Skin

**Carcinogenicity Classification:**

**Quartz Silica Sand (Crystalline Silica):** IARC Group1: Known human carcinogen based on human evidence.

**NTP (National Toxicology Program):** Classified Crystalline Silica as a known human carcinogen.

### 12. ECOLOGICAL INFORMATION (PART B)

**Acute Toxicity for:**

**Fish:** Polyamide Resin: Zebrafish /LC50 (96hrs): >5.0mg/l

**Aquatic Invertebrates:** Polyamide Resin: Water Flea Daphnis/EC 50 (48hrs): > 7.07mg/l

**Algae:** No Data Available

**Microorganisms:** No Data Available

**Mobility:** Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

### 13. DISPOSAL CONSIDERATIONS (PART B)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

# SHEP POXY ROADS & HIGHWAYS MEDIUM VISCOSITY



## 14. TRANSPORT INFORMATION (PART B)

**DOT (US)**

**CARTRIDGE:** Limited Quantity, LTD QTY

**BULK** – Corrosive Liquid, n.o.s. (Amines), Class 8, UN 1760, PG III

**IATA/ICAO**

**CARTRIDGE/BULK:** Corrosive Liquid, n.o.s. (Amines), Class 8, UN 1760, PG III

**IMDG**

**CARTRIDGE/BULK:** Corrosive Liquid, n.o.s. (Amines), Class 8, UN 1760, PG III

**Marine pollutant:** No

## 15. REGULATORY INFORMATION (PART B)

**Further information:** HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings		NFPA ratings	
Health:	2	Health:	2
Flammability:	1	Flammability:	1
Physical hazard:	0	Instability:	0
PPE:	G		



**Hazard Rating:** 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Severe, 4 = Extreme

**Federal Regulations:**

**SARA Title 311/312:** Chronic Health Hazard (Bisphenol A)

**CA Prop 65:** This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**TSCA:** Listed or Exempt

**State Regulations:**

State RTK	Chemical Name	CAS #
NJ, MA, PA	Titanium Dioxide	13463-67-7

## 16. OTHER INFORMATION (PART B)

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard.

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.