



1. PRODUCT AND COMPANY IDENTIFICATION

Company	: EUCLID CHEMICAL COMPANY	Contact person	: EH&S Department
Address	: 19218 REDWOOD ROAD CLEVELAND OH 44110	Material name:	: SUPER DIAMOND CLEAR
Telephone	: 216-531-9222	Product Code	: 359A 55
Emergency Phone	: 800-424-9300 (U.S.) (Chemtrec) 1-613-996-6666 (Canada)	Recommended use	: Coatings
		Restrictions on use	: Not known

2. HAZARDS IDENTIFICATION

Hazard Classification

Physical hazards

Flammable liquids Category 3

Health hazards

Skin Corrosion/Irritation Category 2
 Germ Cell Mutagenicity Category 1B
 Carcinogenicity Category 1B
 Aspiration Hazard Category 1

Unknown toxicity - Health

Acute toxicity, oral 0.2 %
 Acute toxicity, dermal 3.83 %
 Acute toxicity, inhalation, vapor 100 %
 Acute toxicity, inhalation, dust or mist 100 %

Environmental hazards

Acute hazards to the aquatic environment Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment 65.8 %
 Chronic hazards to the aquatic environment 100%

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

Flammable liquid and vapor.	Causes skin irritation.	May cause genetic defects.
May be fatal if swallowed and enters airways.	Toxic to aquatic life.	May cause cancer.

Precautionary statement:

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response:

IF ON SKIN (or hair): Take off all contaminated clothing immediately. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention. Specific treatment (see product label). Take off contaminated clothing. In case of fire: Use fire-extinguishing media appropriate for surrounding materials.

Storage:

Store in well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws, regulations and product characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.



3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Identity	CAS number	Content in percent (%)*
Aromatic petroleum distillates	64742-95-6	30 - 60%
1,2,4-Trimethylbenzene	95-63-6	15 - 40%
1,3,5-Trimethylbenzene	108-67-8	3 - 7%
Xylene	1330-20-7	1 - 5%
Cumene	98-82-8	1 - 5%
Ethylbenzene	100-41-4	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. FIRST AID PROCEDURES

- Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
- Inhalation:** Move to fresh air.
- Skin contact:** Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
- Most important symptoms and effects, acute and delayed:**
Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.
- Indication of any immediate medical attention and special treatment needed:**
Treatment: Symptoms may be delayed.

5. FIRE AND EXPLOSIVES HAZARDS

- General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
- Suitable (and unsuitable) extinguishing media:**
Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.
- Special hazards arising from the chemical:** Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.
- Special protective equipment and precautions for firefighters:**
Special fire fighting procedures: No data available.
- Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, self-contained breathing apparatus (SCBA).



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

- General measures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
- Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
- Notification procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
- Environmental precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Occupational exposure limits			
Chemical Identity	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm	U.S. ACGIH Threshold Limit Values (2011)
1,3,5-Trimethylbenzene	TWA	25 ppm	U.S. ACGIH Threshold Limit Values (2011)
Xylene	TWA	100 ppm	U.S. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	U.S. ACGIH Threshold Limit Values (2011)
Cumene	PEL	100 ppm 435 mg/m ³	U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 ppm	U.S. ACGIH Threshold Limit Values (2011)
Ethylbenzene	PEL	50 ppm 245 mg/m ³	U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm	U.S. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m ³	U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

Chemical Identity	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWAEV	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWAEV	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm 246 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)



8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate engineering controls: Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment:

- General information:** Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin protection:**
 - Hand protection:** Use suitable protective gloves if risk of skin contact.
 - Other:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:		Flash point:	42°C (108°F).
Physical state:	Liquid.		(Setaflash Closed Cup)
Form:	Liquid.	Evaporation rate:	Slower than Ether.
Color:	Colorless.	Flammability (solid, gas):	No.
Odor:	Mild petroleum/solvent.	Upper/lower limit on flammability or explosive limits:	
Odor threshold:	No data available.	Flammability limit - upper (%):	7%(V).
pH:	No data available.	Flammability limit - lower (%):	1%(V).
Melting point/freezing point:	No data available.	Explosive limit - upper (%):	No data available.
Initial boiling point & boiling range:	No data available.	Explosive limit - lower (%):	No data available.



9. PHYSICAL AND CHEMICAL PROPERTIES (CONTINUED)

Vapor pressure:	No data available.	Partition coefficient (n-octanol/water):	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.	Auto-ignition temperature:	No data available.
Relative density:	0.9	Decomposition temperature:	No data available.
Solubility(ies):		Viscosity:	< 20.5 mm ² /s (40°C (104°F))
Solubility in water:	Practically insoluble.		
Solubility (other):	No data available.		

10. STABILITY/REACTIVITY

Reactivity:	No data available.
Chemical stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous decomposition products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects:

Acute toxicity (list all possible routes of exposure):

Oral		Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating.
Product:	ATEmix: 13,097.97 mg/kg	Cumene	in vivo (Rabbit, 24 hrs): Not irritating.
Dermal		Ethylbenzene	Irritating.
Product:	ATEmix: 5,256.8 mg/kg	Respiratory or skin sensitization	
Inhalation		Product:	No data available.
Product:	No data available.	Carcinogenicity	
Specified substance(s):		Product:	May cause cancer.
1,2,4-Trimethylbenzene	LC 50 (Rat, 4 h): 10,200 mg/m ³	IARC monographs on the evaluation of carcinogenic risks to humans:	
1,3,5-Trimethylbenzene	LC 50 (Rat, 4 h): 10,200 mg/m ³	Cumene	Overall evaluation: Possibly carcinogenic to humans.
Xylene	LC 50 (Rat, 4 h): 6,350 mg/l	Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Cumene	LC 50 (Mouse, 7 h): 10 mg/l	U.S. National Toxicology Program (NTP) report on carcinogens:	
Ethylbenzene	LC 50 (Rat): 55 mg/l	Cumene	Reasonably Anticipated to be a Human Carcinogen.
Repeated dose toxicity		U.S. OSHA specifically regulated substances (29 CFR 1910.1001-1050):	
Product:	No data available.	No carcinogenic components identified.	
Skin corrosion/irritation		Germ cell mutagenicity:	
Product:	+No data available.	In vitro	
Serious eye damage/eye irritation		Product:	No data available.
Product:	No data available.		
Specified substance(s):			
Aromatic petroleum distillates	in vivo (Rabbit, 24 - 72 hrs): Not irritating.		
1,2,4-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating.		
1,3,5-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating.		



11. TOXICOLOGICAL INFORMATION (CONTINUED)

In vivo		Specific target organ toxicity - repeated exposure	
Product:	No data available.	Product:	No data available.
Reproductive toxicity:		Aspiration hazard	
Product:	No data available.	Product:	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure		Other effects:	No data available.
Product:	No data available.		

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
1,3,5-Trimethylbenzene	LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Cumene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l Mortality
Ethylbenzene	LC 50 (Bluegill (Lepomis macrochirus), 24 h): 70 - 149 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 66 - 276 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 24 h): 11 - 18 mg/l Mortality

Aquatic invertebrates:

Product:

No data available.

Specified substance(s):

1,2,4-Trimethylbenzene	LC 50 (Scud (Elasmopus pectinicus), 24 h): 4.89 - 5.62 mg/l Mortality
1,3,5-Trimethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication
Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality
Cumene	LC 50 (Water flea (Daphnia magna), 24 h): 95 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Aromatic petroleum distillates	NOAEL (Daphnia magna, 21 d): 2.6 mg/l read across
Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result
Cumene	NOAEL (Danio rerio and Pimephales promelas, 28 d): 0.38 mg/l QSAR

Aquatic invertebrates:

Product:

No data available.

Toxicity to aquatic plants

Product:

No data available.



12. ECOLOGICAL INFORMATION (CONTINUED)

Persistence and Degradability:

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration factor (BCF)

Product: No data available.

Partition coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20
Cumene Log Kow: 3.66
Ethylbenzene Log Kow: 3.15

Mobility in soil:

No data available.

Other adverse effects:

Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated packaging: No data available.

14. TRANSPORTATION INFORMATION

TDG: Not Regulated

CFR / DOT: Not Regulated

IMDG: UN1866, RESIN SOLUTION, 3, PG III

Further information: The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):

None present or none present in regulated quantities.

U.S. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable Quantity
Xylene	100 lbs.
Cumene	5,000 lbs.
Ethylbenzene	1,000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire hazard.
- Immediate (acute) health hazards.
- Delayed (chronic) health hazard.

SARA 302 Extremely Hazardous Substance:

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification:

Chemical Identity	Reportable Quantity
Xylene	100 lbs.
Cumene	5,000 lbs.
Bis (2-propylheptyl) phthalate	
Ethylbenzene	1,000 lbs.

SARA 311/312 Hazardous Chemical:

Chemical Identity	Threshold Planning Quantity
Aromatic petroleum distillates	500 lbs.
1,2,4-Trimethylbenzene	500 lbs.

1,3,5-Trimethylbenzene	500 lbs.
Xylene	500 lbs.
Cumene	500 lbs.
Ethylbenzene	500 lbs.

SARA 313 (TRI Reporting):

Chemical Identity

1,2,4-Trimethylbenzene
Xylene
Cumene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3):

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

U.S. State Regulations:

U.S. California Proposition 65:

This product contains chemical(s) known to the state of California to cause cancer and/or to cause birth defects or other reproductive harm.

U.S. New Jersey Worker and Community Right-to-Know Act:

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
Xylene
Cumene
Diethylbenzene, mixed isomers



15. REGULATORY INFORMATION (CONTINUED)

U.S. Massachusetts RTK - Substance List

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
Xylene
Cumene

U.S. Pennsylvania RTK - Hazardous Substances

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
Xylene
Cumene
Bis (2-propylheptyl) phthalate

U.S. Rhode Island RTK

Chemical Identity

1,2,4-Trimethylbenzene
Xylene
Cumene
Bis (2-propylheptyl) phthalate

Other Regulations:

Regulatory VOC (less water and exempt solvent): 647 g/l
VOC Method 310: 71.94%

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the inventory.
U.S. TSCA Inventory:	All components in this product are listed on or exempt from the inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the inventory.

16. OTHER INFORMATION

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.